Philips
Stereo dubbing cable

6 m

3.5 mm (M) - 3.5 mm (M) Coiled

SWA2529W

Ensure a reliable connection

with this stereo dubbing cable

Depend on this cable to provide you with a reliable audio connection between components.

Enjoy good audio quality
- High-purity copper conductor for reliable signal transfer

Protects against signal loss
- Bare copper shielding

Easy installation
- Colour-coded connectors for instant recognition
- Non-slip ergonomic grip for easy use

Enjoy extended durability
- Moulded plug for secure connections
- Flexible PVC jacket
- Rubber strain relief

PHILIPS

sense and simplicity

Stereo dubbing cable
6 m 3.5 mm (M) - 3.5 mm (M) Coiled

SWA2529W/10

Specifications

Packaging Data
- Quantity: 1
- EAN/UPC/GTIN: 87 10895 99450 7
- Gross weight: 3 kg
- Net weight: 1 kg
- Tare weight: 2 kg

Inner Box
- EAN/UPC/GTIN: 87 10895 99848 2
- Quantity: 6
- Length: 245 mm
- Width: 150 mm
- Height: 105 mm
- Gross weight: 0.38 kg
- Net weight: 0.12 kg
- Tare weight: 0.26 kg

Outer Box
- EAN/UPC/GTIN: 87 10895 99849 9
- Quantity: 36
- Length: 340 mm
- Width: 340 mm
- Height: 265 mm
- Gross weight: 2.78 kg
- Net weight: 0.72 kg
- Tare weight: 2.06 kg

Dimensions
- Product length: 23.5 cm
- Product dimensions (W x H): 95 x 22 mm
- Gross weight: 0.04 kg
- Net weight: 0.02 kg
- Tare weight: 0.02 kg

Product highlights

High-purity copper
This copper conductor provides high accuracy in signal transfer with minimal resistance.

Bare copper shielding
Bare copper shielding protects against signal loss.

Colour-coded connectors
Colour-coded connections make it easy to install your cable into the correct inputs and outputs

Easy grip
This non-slip grip makes connecting your components easy and ergonomically comfortable.

Moulded plug
Moulded plugs ensure secure connections between components and offer extended durability.

Flexible PVC Jacket
Flexible PVC jacket provides protection to the delicate core of the cable. It also offers extended durability and ease of installation.

Rubber strain relief
Rubber strain relief provides a secure yet flexible juncture between the cable and the plug.

Issue date 2008-10-21
Version: 2.0.5
12 NC: 9082 100 09809
EAN: 87 10895 99450 7

© 2008 Koninklijke Philips Electronics N.V.
All Rights reserved.
Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com